

INDIVIDUAL DIAGNOSIS MODE

The DPD series models have an internal menu accessible through a combination of Keys. This menu allows the user to put the module in local mode for maintenance / diagnosis without affecting the rest of the system in operation.

EASY INSTALLATION



DPDs to control SKUs DPA1/DPM1

Product overview

The DPA1/DPM1 is perfect for being placed in front of the SKU, given its dimensions and characteristics. Its 4 digits allow us to visualize characters and numbers during order picking.

Description

The PLA1 is characterized by having 4 alphanumeric digits or a maximum of 30 in scroll. Furthermore, It has a membrane keypad with 4 keys and a RGB pilot capable of generating up to 7 colors. The pilot has a light diffuser shell designed for long-distance signaling and perfect for hallways. To facilitate operator ergonomics, features an audible signal (buzzer), which is configurable. In addition in installations with high quality requirements, it includes a digital input signal.

Specifications

Power supply:	24VDC
Vin _{max} :	35VDC
Vin _{min} :	9VDC
Maximum Power:	700mW
Technology:	Electrotec
Protocol:	RS485 – Electrotec
Topology:	Ring – Master/Slave
Connection:	Cable FTP – RJ45
Signaling:	Leds RGB 23mmØ Shell
Screen:	60x22mm 4 alfa digits. Red color
Keypad:	Membrane Key + Key – Validation key Function key
Alarm:	Audible
Digital Input:	PNP
Dimensions:	161x36mm
IP Code:	IP 63
Operating temperature:	-20º/40º
Protections:	Fuse SMD